

ABSTRACT OF THE DISCLOSURE

A pin removal and placement tool (50) has a body member (52) made of plate steel having a contact surface (52b) and a rear edge (52c). Tool (50) also may have an anvil plate (54) mounted on a striking plate (56), a drive shaft (58), and a handle (70) projecting at a right angle from the body member (52). The striking plate (56) is fixedly mounted to the rear edge (52c) and anvil plate (54) is disposed at a selected angle to the drive shaft (58) to enhance the striking force of drive shaft (58) and to reduce the length of the tool (50) so as to facilitate its insertion between the teeth of buckets, etc. A shoe (62) may be mounted on tool (5) to adjust the clearance between contact surface (52b) and drive shaft (58). The handle (70) may be either removably or fixedly attached to the body member (52) and be dimensioned and mounted to selectively project from a selected side thereof, or from both sides thereof.

10  
20  
30  
40  
50  
60  
70  
80  
90  
100  
110  
120  
130  
140  
150  
160  
170  
180  
190  
200  
210  
220  
230  
240  
250  
260  
270  
280  
290  
300  
310  
320  
330  
340  
350  
360  
370  
380  
390  
400  
410  
420  
430  
440  
450  
460  
470  
480  
490  
500  
510  
520  
530  
540  
550  
560  
570  
580  
590  
600  
610  
620  
630  
640  
650  
660  
670  
680  
690  
700  
710  
720  
730  
740  
750  
760  
770  
780  
790  
800  
810  
820  
830  
840  
850  
860  
870  
880  
890  
900  
910  
920  
930  
940  
950  
960  
970  
980  
990  
1000